



**Much more than just
water filters**

Installation Guide – Wellness Shower Filter



Will the shower filter fit into my existing shower?

The **Wellness Shower** is designed to fit all standard USA bathroom fittings. All you need to do is remove the existing shower rose and replace it with the **Wellness Shower**. You may then chose to use your own rose (max pressure rating 2.5 gpm). Shower arms with unusually large diameters will require adaptor.

Use plumbers tape to stop any drips. It is standard procedure for all showers to apply plumbers tape around the threads to prevent annoying drips.

What about my rain head shower attachment or power shower?

Some rain heads and custom shower fittings may require adaptors to connect the filter's standard-size threads to unusual-sized shower arms for example. If in doubt, please send us a digital photo of your shower and we will try our best to advise you. A full refund is given should the shower filter not fit for any reason.

My shower arm is really close to the ceiling. How much clearance do I need?

The filter can be positioned at 45% angle and still work fine. It will not work if the shower filter is lying horizontal. You really need at least 8 inches clearance.

How do I know when to change the filter?

The Wellness shower filter lasts for 27,000 gallons. That's equivalent to 1,080 ten minute showers – three a day for a year for example. You may also notice chlorine odor returning, your skin will feel more dry.

Explain backwashing: This flushes the filter of mineral deposit build up and extends life. Simply rotate the **Wellness Shower** cartridge around to the marker and turn on the cold water for 30-60 seconds. Rotate the cartridge back around to its service position and you are ready to go.

How easy is it to replace the cartridge? Replacing the **Wellness Shower** cartridge takes less that 3 minutes. Simply remove the locking ring, lift the old cartridge out - swap it for the new - and replace the locking ring.